

LTV angle screwdriver models have a fast, accurate shut-off clutch and are designed for durability.

- Slim design of the angle head allows good access in limited spaces and awkward positions.
- Spiral cut gears give high accuracy.

RE reporting conversion kits are available for LTV screwdriver models. For kit, see accessory page.



LTV009

Model	Torque range soft joint		Free speed r/min	Weight		Length mm	Angle head height mm	Angle head center to side mm	Air consumption at free speed		Rec. hose size mm	Air inlet thread in	Ordering No.
	Nm	in lb		kg	lb				l/s	cfm			
<b>1/4" female hexagon drive for bits</b>													
LTV009 R05-42	0,4-5	3,5-44,2	850	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 07
LTV009 R07-42	1,1-7	9,7-61,9	500	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 10
LTV009 R07-42-SH	1,1-7	9,7-61,9	500	0,7	1,5	243	25	9	6	13	6	1/8	8431 0279 29
LTV009 R09-42	1,3-9	11,5-79,6	430	0,7	1,5	266	28,5	11	6	13	6	1/8	8431 0278 15
LTV009 R11-42	1,3-11	11,5-97,3	320	0,8	1,8	266	28,5	11	6	13	6	1/8	8431 0278 21
LTV009 R035-42	0,4-3,5	3,5-31	1100	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 04
LTV19 R15-42	6-15	54-133	360	1,1	2,4	309	36	11	7	15	8	1/4	8431 0279 35
<b>1/4" square drive for sockets</b>													
LTV009 R05-6	0,4-5	3,5-44,2	850	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 08
LTV009 R07-6	1,1-7	9,7-61,9	500	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 11
LTV009 R07-6-SH	1,1-7	9,7-61,9	500	0,7	1,5	243	25	9	6	13	6	1/8	8431 0279 28
LTV009 R07-6-230	0,3-7	2,6-61,9	230	0,8	1,8	266	25	9	6	13	6	1/8	8431 0279 18
LTV009 R09-6	1,3-9	11,5-79,6	430	0,7	1,5	266	28,5	11	6	13	6	1/8	8431 0278 17
LTV009 R11-6-200	1,3-11	11,5-97,3	200	0,7	1,5	266	28,5	11	6	13	6	1/8	8431 0279 32
LTV009 R11-6-200-B	1,3-11	11,5-97,3	200	0,8	1,8	266	27,6	11	6	13	6	1/8	8431 0278 31
LTV009 R11-6	1,3-11	11,5-97,3	320	0,8	1,8	266	28,5	11	6	13	6	1/8	8431 0278 22
LTV009 R035-6	0,4-3,5	3,5-31	1100	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 05
LTV19 R15-6	6-15	54-133	360	1,1	2,4	309	31	11	7	15	8	1/4	8431 0279 34
<b>3/8" square drive for sockets</b>													
LTV009 R03-10	0,7-3	6,2-26,5	1400	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 23
LTV009 R09-10	1,3-9	11,5-79,6	430	0,7	1,5	266	28,5	11	6	13	6	1/8	8431 0278 13
LTV009 R11-10	1,3-11	11,5-97,3	320	0,8	1,8	266	28,5	11	6	13	6	1/8	8431 0278 20
LTV19 R15-10	6-15	54-133	360	1,1	2,4	309	31	11	7	15	8	1/4	8431 0279 36
<b>1/4" quick change chuck</b>													
LTV009 R05-Q	0,4-5	3,5-44,2	850	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 06
LTV009 R07-Q	1,1-7	9,7-61,9	500	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 09
LTV009 R07-Q-SH	1,1-7	9,7-61,9	500	0,7	1,5	243	25	9	6	13	6	1/8	8431 0279 30
LTV009 R09-Q	1,3-9	11,5-79,6	430	0,7	1,5	266	28,5	11	6	13	6	1/8	8431 0278 12
LTV009 R11-Q	1,3-11	11,5-97,3	320	0,8	1,8	266	28,5	11	6	13	6	1/8	8431 0278 19
LTV009 R025-Q	0,6-2,5	5,3-22,1	1650	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 00
LTV009 R035-Q	0,4-3,5	3,5-31	1100	0,7	1,5	266	25	9	6	13	6	1/8	8431 0278 03
LTV19 R15-Q	6-15	54-133	360	1,1	2,4	309	45	11	7	15	8	1/4	8431 0279 37
<b>Flush socket</b>													
LTV009 R12-FS-10	1,5-8	13,3-70,8	340	1,1	2,4	261	23,5	13,5	6	13	6	1/8	8431 0632 11

- All models:**
- Are reversible.
  - All data at an air pressure of 6.3 bar.
  - Are ESD approved

## Accessories Included

### EXHAUST HOSE

Included with straight and air-on-top models

### CLUTCH ADJUSTMENT KEY

Included with all shut-off and slip clutch tools



Clutch adjustment key

## Optional Accessories



Designation	Exhaust hose	Support handle	ESD hose	Torque arms adapters	Installation proposal	ESD approved pistol handle
LUM12 HRX/HRF	4210 2052 00	4110 1355 92	8202 0501 06	–	8202 1180 67	4210 3616 04
LUM22 HR 3, 4, 6	4210 2052 00	4110 1355 92	8202 0501 10	–	8202 1180 77	4210 4337 04
LUM22 HR 10, 12	4210 2052 00	4110 1355 93	8202 0501 10	–	8202 1180 77	4210 4337 04
LUM22 HRX 3, 4, 6	4210 2052 00	4110 1355 92	8202 0501 10	–	8202 1180 77	4210 3616 04
LUM12 SR	4210 2052 00	–	8202 0501 06	4390 1735 52	8202 1180 67	–
LUM12 PR	4210 2052 00	–	8202 0501 06	4390 1735 53	8202 1180 67	–
LUM22 SR	4210 2053 00	–	8202 0501 10	4390 1735 51	8202 1180 77	–
LUM22 PR	4210 2053 00	–	8202 0501 10	4390 1735 54	8202 1180 77	–
LTV009	4210 2052 00	–	8202 0501 06	–	8202 1180 67	–
LUM32 HR	4210 2052 00	4110 1355 94	8202 0501 10	–	8202 1180 77	4210 4337 04
LUF34	4210 2053 00	4110 1355 82	8202 0501 10	–	8202 1180 77	–

Model	Ordering No.
<b>Threaded clutch houses</b>	
LUM12 PR/SR 1, 2, 3, 4	4210 4386 04
LUM12 HRX/HRF 1, 3, 5, 8	4210 4386 04
LUM22 HRX/HR 2, 3, 4, 6	4210 4386 04
LUM22 HRX/HR 10, 12	4210 4392 03
LUM22 SR/PR 3, 4, 5, 6, 8	4210 4383 04
LUM22 SR/PR 10, 12	4210 4383 03
<b>Angle head covers</b>	
LTV009 R025-R07	4210 4115 00
LTV009 R08-R11	4210 4116 00
<b>Protective covers</b>	
LUM22/32 HR	4210 3150 00
LUM22 HRX	4210 3151 00
LUM12 HRX	4210 4642 00
<b>Threaded fronts</b>	
LUM 32 HR10, 15	4210 4252 90
Suspension yoke for LTV009	4210 4461 80
Quick change chuck kit, extra wide diameter for easy handling	4210 2326 91
Angle-head for LTV009 R03/08/09/11, 90° hex drive magnetic bit holder <sup>a</sup>	4210 3857 91



Suspension yoke



Quick change chuck kit



Angle-head for LTV009

<sup>a</sup> Substitute for 4210 3857 XX angle heads.

### RE-CONVERSION KITS

Model	Ordering No.
LUM12 HRF	4210 3624 99
LUM12 SR	4210 4137 90
LUM22 SR	4210 2057 80
LTV009	4210 4137 90