

The TWIST and LUF pistol grip range comes in several different configurations:

- HR: Model with traditional-grip can be used with high grip when feed force is needed or with low grip for minimal reaction force.
- HRX: models with balanced grip are perfectly balanced for standard pistol grip applications.
- HRF: Balanced grip with multiple air inlets for flexible connection.



Model	Torque range soft joint		Free speed r/min	Weight		Length mm	CS distance mm	Air consumption at free speed		Rec. hose size mm	Air inlet thread in	Ordering No.
	Nm	in lb		kg	lb			l/s	cfm			
<b>With trigger and push start</b>												
TWIST12 HRX2	0,6-2,4	5,3-21,2	1650	0,65	1,4	176	15	6,5	14	6	1/8	8431 0278 40
TWIST12 HRX3	0,6-3,5	5,3-31,0	1150	0,65	1,4	186	15	6,5	14	6	1/8	8431 0278 39
TWIST12 HRX4	0,5-4,4	4,4-38,9	800	0,65	1,4	186	15	6,5	14	6	1/8	8431 0278 38
TWIST22 HRX7	1,5-7,5	13,3-66,4	1100	1,05	2,3	205	15	9	19	8	1/4	8431 0269 26
TWIST22 HRX10	1,5-10	13,3-88,5	750	1,1	2,4	205	15	9	19	8	1/4	8431 0269 27
TWIST22 HRX12	5-12	44,2-106,2	500	1,05	2,3	205	15	9	19	8	1/4	8431 0269 28
TWIST22 HR3	1,0-3,5	8,9-31	2100	0,95	2,1	195	15	8	17	8	1/4	8431 0278 86
TWIST22 HR6	2,2-6,5	19,5-57,5	1600	0,95	2,1	195	15	8	17	8	1/4	8431 0269 70
TWIST22 HR7	1,5-7,5	13,3-66,4	1150	0,95	2,1	195	15	8	17	8	1/4	8431 0269 14
TWIST22 HR10	1,5-10,0	13,3-88,5	750	1	2,2	205	15	8	17	8	1/4	8431 0269 15
TWIST22 HR12	5,0-12,0	44,2-106,2	500	1	2,2	195	15	8	17	8	1/4	8431 0269 16
LUF34 HR04	3,0-17,0	27,0-150,0	440	1,4	3,1	265	21	9,5	19	8	1/4	8431 0311 05
LUF34 HR08	2,0-15,0	18,0-133,0	750	1,4	3,1	265	21	9,5	19	8	1/4	8431 0311 09
LUF34 HR16	3,0-12,0	27,0-107,0	1600	1,4	3,1	265	21	9,5	19	8	1/4	8431 0311 17
<b>Multiple air inlet models and air-on-top models with trigger start and push start</b>												
TWIST12 HRF4	0,5-4,4	4,4-38,9	850	0,7	1,5	200	15	6,5	14	6	1/8	8431 0269 40

**All models:** Are reversible.  
 Are equipped with a 1/4" female hexagon drive for bits.  
 Have quick change chuck.  
 All data at an air pressure of 6.3 bar.